

MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Supershine® Black Fast Drying Hoof Polish & Sealer

GENERAL USE: Hoof Polish and Sealer

PRODUCT DESCRIPTION: Black flammable liquid, acetone odor



MANUFACTURER'S NAME

W. F. Young, Inc.

DATE PREPARED: December 16, 2008

SUPERSEDES: New

Page 1 of 4

ADDRESS (NUMBER, STREET, P.O. BOX)

302 Benton Drive

TELEPHONE NUMBER FOR INFORMATION

(413) 526-9999

(CITY, STATE AND ZIP CODE)

East Longmeadow, MA 01028

COUNTRY

USA

EMERGENCY TELEPHONE NUMBER

(413) 526-9999

SECTION 2 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Black liquid, extremely flammable, potentially hazardous vapors. Contains a phenolic resin that inherently contains a small amount of phenol. Can cause eye and skin irritation upon contact. Inhalation of vapors can cause anesthetic effect leading to death in poorly ventilated areas. Hazard Symbols for this product - F, Xi Risk Phrases - R11,36, 66, 67.

POTENTIAL HEALTH EFFECTS

INHALATION: High concentrations are irritating to the respiratory tract; may cause headache, dizziness, nausea, vomiting and malaise.

SKIN: Brief contact may cause slight irritation; prolonged contact may cause moderate reddening, swelling and possible necrosis.

EYES: Contact causes severe irritation and pain associated with redness and swelling of the conjunctiva.

INGESTION: Moderately toxic; may cause headache, dizziness, diarrhea and general weakness; large doses may result in red blood cell hemolysis.

CARCINOGENICITY

NTP?

No

IARC MONOGRAPHS?

Yes

OSHA REGULATED?

No

IARC classifies Phenol as Group 3, limited or inadequate evidence of carcinogenicity.

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

HAZARDOUS COMPONENTS	CAS #	EINECS #	% (by weight)	OSHA PEL		ACGIH TWA		RQ LBS
				PPM	MG/M3	PPM	MG/M3	
Acetone (b,c)	67-64-1	200-662-2	70 - 80	750	800	500		5000
Phenol (a,b,c,d,e,f)	108-95-2	203-632-7	0.4 - 0.6	5	19	5	19	1000

The remaining components of this product are non-hazardous or are in small enough quantities as to not meet regulatory thresholds for disclosure. These components contain no substances or impurities which would influence the classification of this product.

(a,c) See Section 15

(b) Indicates that the Resource Conservation and Recovery Act (RCRA) has determined the waste for this chemical is listed as hazardous and must be handled according to regulations in 40 CFR 260-281.

(d) Indicates an Extremely Hazardous Substance, if your facility has a designated amount of this substance, Threshold Planning Quantity (TPQ) in inventory, the regulations of 40 CFR 355 and 370 apply, including submission of Tier I / Tier II forms every March 1.

(e) Indicates substance appears on National Toxicology Program (NTP) list of carcinogens, International Agency for Research on Cancer (IARC) list of carcinogens or is regulated by the Occupational Safety and Health Administration (OSHA) as a possible carcinogen.

(f) Indicates an employee's skin exposure shall be prevented or reduced to the extent necessary in the circumstances through the use of gloves, coveralls, goggles, or other appropriate equipment.

MATERIAL SAFETY DATA SHEETPRODUCT NAME: Supershine® Black Fast Drying Hoof Polish & Sealer
December 16, 2008

Page 2 of 4

SECTION 4 - FIRST AID MEASURES**INHALATION:** Remove affected person to fresh air; provide oxygen if breathing is difficult; if affected person is not breathing, administer CPR and seek emergency medical attention.**SKIN:** Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention.**EYES:** Check for and remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; if irritation persists, seek medical attention.**INGESTION:** Give two glasses of water for dilution; Induce vomiting by sticking fingers down throat; never give anything by mouth to an unconscious person; seek medical attention.**SECTION 5 - FIRE FIGHTING MEASURES****FLASH POINT (METHOD USED)**

20.3° F (-6.5° C) TCC

FLAMMABLE LIMITS

LEL: 2.6%

UEL: 12.8%

AUTOIGNITION TEMPERATURE:

869° F (465° C)

NFPA CLASS: IA**GENERAL HAZARDS:** Product is flammable. Products of combustion include compounds of carbon, hydrogen and oxygen, including carbon monoxide.**EXTINGUISHING MEDIA**

Carbon dioxide, water, water fog, dry chemical, chemical foam.

FIRE FIGHTING PROCEDURESSelf - contained respiratory equipment; cool containers to prevent pressure buildup and possible explosion when exposed to extreme heat.
Caution - material is flammable!**UNUSUAL FIRE AND EXPLOSION HAZARDS**

Closed containers can explode due to buildup of pressure when exposed to extreme heat. Vapors may cause a flash fire or ignite explosively. Vapors may travel a considerable distance to a source of ignition and flash back.

HAZARDOUS COMBUSTION PRODUCTS

Smoke, fumes or vapors, oxides of carbon.

SECTION 6 - ACCIDENTAL RELEASE MEASURES**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** COMBUSTIBLE - Evacuate and ventilate area; remove all sources of sparks, ignition and open flames; confine and absorb into approved absorbent; place material into approved containers for disposal; do not wash to sewer or waterway.**SECTION 7 - HANDLING AND STORAGE****PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:** This material is combustible. It should be stored in tightly closed containers in a cool, well ventilated area. Vapor may form explosive mixtures in air. All sources of ignition should be controlled. This material may be classified as Flammable liquids, n.o.s. UN 1993 if transported by vessel or aircraft. Certain exemptions may qualify for shipping as ORM-D. Refer to 49 CFR 173.120. Keep this and other chemicals out of reach of children. Avoid inhaling concentrated fumes or vapors.**SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION****ENGINEERING CONTROLS**

The use of local exhaust ventilation is recommended to control emissions near the source. Provide mechanical ventilation of confined spaces. Use explosion-proof ventilation equipment.

PERSONAL PROTECTION:**RESPIRATORY PROTECTION:** None required while threshold limits are kept below maximum allowable concentrations; if TWA exceeds limits, NIOSH approved respirator must be worn. Refer to 29 CFR 1910.134, ANSI Z88.2, or European Standard EN 149 for complete regulations.**PROTECTIVE GLOVES:** Neoprene, butyl or nitrile rubber gloves with cuffs.**EYE PROTECTION:** Chemical splash goggles. Refer to 29 CFR 1910.133, ANSI Z87.1, or European Standard EN166.**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:** Safety eyewash station nearby.**WORK / HYGIENIC PRACTICES:** Practice safe workplace habits. Minimize body contact with this, as well as all chemicals in general.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Supershine® Black Fast Drying Hoof Polish & Sealer
December 16, 2008

Page 3 of 4

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR Black liquid, acetone odor	VAPOR DENSITY (AIR = 1) > 1
SPECIFIC GRAVITY (WATER = 1) 0.865	EVAPORATION RATE (Water = 1) < 1
SOLUBILITY IN WATER Highly miscible	% VOLATILE (BY WEIGHT) 78%
pH Not applicable	VAPOR PRESSURE 184 mm Hg @ 20° C
BOILING POINT 133° F (56.1° C)	FREEZING POINT Not determined
VISCOSITY Slightly viscous	VOLATILE ORGANIC COMPOUNDS (VOC's) 5.05 pounds / gallon (601 grams / liter)

SECTION 10 - STABILITY AND REACTIVITY

STABILITY UNSTABLE: STABLE: X	CONDITIONS TO AVOID: Extreme temperatures, open flames.
INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers, strong acids.	
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes or vapors, and smoke may be produced.	
HAZARDOUS POLYMERIZATION MAY OCCUR: WILL NOT OCCUR: X	CONDITIONS TO AVOID: None

SECTION 11 - TOXICOLOGICAL INFORMATION

Hazardous Ingredients	CAS #	EINECS #	LD50 of Ingredient Species and Route	LC50 of Ingredient Species
Acetone (b,c)	67-64-1	200-662-2	5800 mg / kg Oral - rat	50,100 ppm / 8H Inhalation - rat
Phenol (a,b,c,d,e,f)	108-95-2	203-632-7	317 mg / kg Oral - rat	82 ppm Inhalation - rat
(a,c) See Section 15				

SECTION 12 - ECOLOGICAL INFORMATION

No data are available on the adverse effects of this material on the environment. Neither COD nor BOD data are available. Based on the chemical composition of this product it is assumed that the mixture can be treated in an acclimatized biological waste treatment plant system in limited quantities. However, such treatment should be evaluated and approved for each specific biological system. None of the ingredients in this mixture are classified as a Marine Pollutant.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations. This product may produce hazardous vapors in a closed disposal container creating a dangerous environment. Refer to 40 CFR 260 - 299 for complete waste disposal regulations. Consult your local, state, or federal agency before disposing of any chemicals. Do not flush to sanitary sewer or waterway. According to the European Waste Catalogue, waste codes are application specific and should be assigned by the user based on the application for which the product is used.

SECTION 14 - TRANSPORT INFORMATION

PROPER SHIPPING NAME: Consumer Commodity

DOT HAZARD CLASS / Pack Group: ORM - D / None
REFERENCE: 49 CFR 173.144- 156
UN / NA IDENTIFICATION NUMBER: None (domestic US only)
LABEL: None Required
HAZARD SYMBOLS: None

IATA HAZARD CLASS / Pack Group: 3.3
IMDG HAZARD CLASS: 3.3
RID/ADR Dangerous Goods Code: 3.3
UN TDG Class / Pack Group: 3.3
Hazard Identification Number (HIN): None

Note: Transportation information provided is for reference only. Customer is urged to consult 49 CFR 100 - 177, IMDG, IATA, EC, United Nations TDG, and WHMIS (Canada) TDG information manuals for detailed regulations and exceptions covering specific container sizes, packaging materials and methods of shipping.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Supershine® Black Fast Drying Hoof Polish & Sealer
December 16, 2008

SECTION 15 - REGULATORY INFORMATION

TSCA (Toxic Substance Control Act)

All components of this product are listed on the U.S. Toxic Substances Control Act Chemical Inventory (TSCA Inventory) or are exempted from listing because a Low Volume Exemption has been granted in accordance with 40 CFR 723.50.

SARA TITLE III (Superfund Amendments and Reauthorization Act)

311/312 Hazard Categories
Immediate health, fire hazard

313 Reportable Ingredients:

(a) Indicates a toxic chemical subject to annual reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

CERCLA (Comprehensive Response Compensation and Liability Act)

(c) The Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) has notification requirements for releases or spills to the environment of the Reportable Quantity (RQ for this mixture = 7,000 lbs) or greater amounts, according to 40 CFR 302.

California Prop 65, Safe Drinking Water and Toxic Enforcement Act of 1986

There are no reportable chemicals present known to the state of California to cause cancer or reproductive toxicity.

CPR (Canadian Controlled Products Regulations)

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations. WHMIS Classification: B2, D2B

IDL (Canadian Ingredient Disclosure List)

Components of this product identified by CAS number and listed on the Canadian Ingredient Disclosure List are shown in Section 3.

DSL / NDSL (Canadian Domestic Substances List / Non-Domestic Substances List)

Components of this product identified by CAS number are listed on the DSL or NDSL, or are otherwise in compliance with the New Substances Notification (NSN) regulations. Only ingredients classified as "hazardous" are listed in Section 3 unless otherwise indicated.

EINECS (European Inventory of Existing Commercial Chemical Substances)

Components of this product identified by CAS numbers are on the European Inventory of Existing Commercial Chemical Substances.

WGK Water Quality Index: 1

VbK Index: A I

Risk Phrases

R11 Highly flammable.
R36 Irritating to eyes.
R66 Repeated exposure may cause skin dryness or cracking.
R67 Vapours may cause drowsiness and dizziness.

SYMBOL(S) REQUIRED FOR LABEL

Flammable Irritant



Safety Phrases

S9 Keep container in a well-ventilated place.
S16 Keep away from sources of ignition.
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

SECTION 16 - OTHER INFORMATION

Specific toxicity tests have not been conducted on this product. Our hazard evaluation is based on information from similar products, the ingredients, technical literature, and/or professional experience.

HMIS HAZARD RATINGS

HEALTH	2*	* = Chronic Health Hazard	2 = MODERATE
FLAMMABILITY	3	0 = INSIGNIFICANT	3 = HIGH
PHYSICAL HAZARD	0	1 = SLIGHT	4 = EXTREME

PERSONAL PROTECTIVE EQUIPMENT B Safety Glasses, Gloves

REVISION SUMMARY:

This MSDS has been revised in the following sections:
No changes noted

MSDS Prepared by:

Comprehensive Data Base, Inc.
P.O. Box 686
Seffner, FL 33583 USA
(863) 644 - 3298 www.compdatabase.com or www.msds.cc

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Any questions regarding this product should be directed to the manufacturer of the product as described in Section 1.